



GRP (Glass-fibre Reinforced Polyester) enclosures

Polyester enclosures are designed to meet the high requirements of mining-, petrochemical-, construction-, and shipbuilding industries. They are highly resistant against most solvents and acids which makes them suitable for refineries and other chemically aggressive surroundings like road tunnels. They are also difficult to ignite and self-extinguishing. The enclosures comply with the protection class IP 65 or 66 depending on the gasket used. The lid screws cannot be lost and are made of stainless steel.



Dimensions mm (LengthxWidthxHeight):

Type	Length	Width	Height
CSP 080806	80	75	55
CSP 080808	80	75	75
CSP 081106	110	75	55
CSP 081606	160	75	55
CSP 081906	190	75	55
CSP 121209	122	120	90
CSP 122209	220	120	90
CSP 161609	160	160	90
CSP 162609	260	160	90
CSP 163609	360	160	90
CSP 202512	250	200	120
CSP 252512	255	250	120
CSP 252516	255	250	160
CSP 402512	400	250	120
CSP 402516	400	250	160
CSP 404012	400	400	120
CSP 602512	600	250	120
CSP 602516	600	250	160

Glass fibre reinforced compressed enclosure base and cover.

IP 65 protection. Weather and shock resistant, flame proof.

Environmental temperature -25 °C +200 °C

Color: RAL 7000 – grey, RAL 7032 – beige, RAL 9005 – black (anti-static). Unique colors for orders!

MEEI license number: D1811V098 MSZ EN 60439-1:2000

CSE type distribution boxes

Glass fibre reinforced compressed enclosure base and cover.

IP 65 protection. Weather and shock resistant, flame proof.

Environmental temperature -25 °C +200 °C

Color: RAL 7000 – grey, RAL 7032 – beige, RAL 9005 – black (anti-static). Unique colors for orders!

MEEI license number: D1471V119MSZ EN 60439-3:2000

Can be used to build in sockets, circuit breakers, Fi relays, and switches. Can be customized as the customer demands.



The protection of the CSE type distribution boxes can be down to IP 44 depending on the protection of the built in parts.

We can assemble unique distribution boxes to meet your personal requirements, the protection of the boxes can be IP 65!

CSE portable distribution boxes

Glass fibre reinforced compressed enclosure base and cover.

IP 65 protection. Weather and shock resistant, flame proof.

Environmental temperature -25 °C +200 °C

Color: RAL 7000 – grey, RAL 7032 – beige, RAL 9005 – black (anti-static). Unique colors for orders!

MEEI license number: D1471V119 MSZ EN 60439-3:2000

Can be used to build in sockets, circuit breakers, Fi relays, and switches. Can be customized as the customer demands.



The protection of the CSE type distribution boxes can be down to IP 44 depending on the protection of the built in parts.

We can assemble unique distribution boxes to meet your personal requirements, the protection of the boxes can be IP 65!